


Material Safety Data Sheet

BRIWAX
INT'L., INC.



BY APPOINTMENT TO
H.M. QUEEN ELIZABETH II
MANUFACTURERS OF
FRENCH POLISHES & LAQUERS
J W BOLLON & Co. LTD.
T/A HENRY FLACK (1860) LTD

 Instructions	This Data Sheet contains Important Information. READ AND KEEP FOR REFERENCE.
---------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------

1.0 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: 1007 (I3) BRIWAX Staynwax Liquid Wax

Product Code: 1007 (I3)

Manufacturer/Supplier:

BRIWAX International Inc. P.O. Box 865110 Plano, TX 75086-5110 1-800-5-BRIWAX Fax: 972-867-8960	2222 Spring Creek Pkwy. Suite 105 Plano, TX 75023
-------------------------------------------------------------------------------------------------------------	---------------------------------------------------------

Transportation Emergencies: Call Chemtrec, 1-800-424-9300

Revision Number: 3/2001- I

Intended use: Coating / Sealer

2.0 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Ethanol	10-30	64-17-5	1000 ppm TWA; 1900 mg/m ³ TWA
Ammonia Solution	1-5	7664-41-7	50 ppm TWA; 35 mg/m ³ TWA
Methyl Alcohol	1-5	67-56-1	200 ppm TWA; 260 mg/m ³ TWA

3.0 HAZARDS IDENTIFICATION

Emergency Overview	Moderate eye irritant. Causes mild skin irritation. Harmful by inhalation. Harmful if Swallowed. Highly Flammable.
Routes of Entry	Contact, Absorption
Target Organs Potentially Affected by Exposure	Eyes, Respiratory Tract, Skin, Nervous System, Digestive Tract
Chemical Interactions that Change Toxicity:	None Known.
Medical Conditions Aggravated by Exposure:	Eye disease; Respiratory disease including asthma and bronchitis; Skin disease including eczema and sensitization, Digestive tract disease.

P.O. Box 865110 Plano, TX 75086
<http://www.briwax.com>
Copyright 2004, BRIWAX Int'l., Inc.

3.0 HAZARDS IDENTIFICATION CONT'D

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Avoid breathing vapors or mists. May cause asphyxiation in high concentrations.
Inhalation Toxicity	Harmful!! Can cause systemic damage (see "Target Organs")
Skin Contact	Can cause minor skin irritation, defatting and dermatitis. Prolonged or repeated contact may produce defatting of the skin leading to irritation and dermatitis.
Skin Absorption	May cause irritation and minor systemic damage.
Eye Contact	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation	Mildly irritating to mouth, throat, and stomach. Can cause abdominal discomfort.
Ingestion Toxicity	Toxic if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects

Carcinogenicity	None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA
Reproductive and Developmental Toxicity	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

4.0 FIRST AID MEASURES

Inhalation	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
Eyes	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention .
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion	Minimal risk of harm is swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this MSDS. Never give anything by mouth to an unconscious person.
Notes to Doctor:	No additional first aid information available.

P.O. Box 865110 Plano, TX 75086
<http://www.briwax.com>
Copyright 2004, BRIWAX Int'l., Inc.

5.0 FIRE FIGHTING MEASURES

Flammability Summary:	Highly Flammable
Extinguishing Media	Dry chemical ; Alcohol foam; Water spray, Halon
Fire and/or Explosion Hazards	Vapors may be ignited by sparks, flames, or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.
Fire Fighting Methods and Protection	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.
Hazardous Combustion Products	Carbon dioxide; Carbon monoxide
Flash Point	21C; 70F
Lower Flammable/Explosive Limit, % in air	3.5

6.0 ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up	Prevent the spread of any spill to minimize harm to human health and the environment is safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

7.0 HANDLING AND STORAGE

Handling Technical Measures and Precautions	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Avoid contact with material. Ground and bond containers when transferring material. Keep in air-tight containers—material is hygroscopic. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse. Use spark-proof tools and explosion-proof equipment.
----------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

7.0 HANDLING AND STORAGE CONT'D

Storage Technical Measures and Conditions	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container closed when not in use.
--------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------

8.0 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.
Respiratory Protection	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 190.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.
Eye Protection	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where use can result in skin contact, practice good personal hygiene.
Gloves	Butyl rubber, Neoprene, Nitrile

Control Parameters

Chemical Name	ACGIH TLV-TWA	ACGIH STEL
Ethanol	1000 ppm TWA; 1880 mg/m ³ TWA	
N-Propyl alcohol	200 ppm TWA; 492 mg/m ³ TWA	250 ppm STEL; 614 mg/m ³ STEL
Methanol	200 ppm TWA; 262 mg/m ³ TWA	250 ppm STEL; 328 mg/m ³ STEL

9.0 PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Colorless to pale amber
Odor	Mild
pH	Not applicable
Solubility in Water	Moderate; 50-99%
Octanol/Water Partition Coefficient	-0.3
Vapor Density	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Volatile Organic Chemicals	651 g/l

P.O. Box 865110 Plano, TX 75086
<http://www.briwax.com>
Copyright 2004, BRIWAX Int'l., Inc.

7.0 HANDLING AND STORAGE CONT'D

Storage Technical Measures and Conditions	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container closed when not in use.
--------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------

8.0 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.
Respiratory Protection	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 190.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.
Eye Protection	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where use can result in skin contact, practice good personal hygiene.
Gloves	Butyl rubber, Neoprene, Nitrile

Control Parameters

Chemical Name	ACGIH TLV-TWA	ACGIH STEL
Ethanol	1000 ppm TWA; 1880 mg/m ³ TWA	
N-Propyl alcohol	200 ppm TWA; 492 mg/m ³ TWA	250 ppm STEL; 614 mg/m ³ STEL
Methanol	200 ppm TWA; 262 mg/m ³ TWA	250 ppm STEL; 328 mg/m ³ STEL

9.0 PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Colorless to pale amber
Odor	Mild
pH	Not applicable
Solubility in Water	Moderate; 50-99%
Octanol/Water Partition Coefficient	-0.3
Vapor Density	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Volatile Organic Chemicals	651 g/l

P.O. Box 865110 Plano, TX 75086
<http://www.briwax.com>
Copyright 2004, BRIWAX Int'l., Inc.

13.0 DISPOSAL CONSIDERATION

Waste Description for Spent Product	Spent or discarded material is hazardous waste.
Disposal Methods	Dispose of by incineration following Federal, State, Local and Provincial regulations.
EPA Waste Code(s)	If discarded this product is considered a RCRA ignitable waste, D001.
Substances subject to EPA Land Ban	U154- Methyl alcohol.

14.0 TRANSPORTATION INFORMATION

DOT Basic Description: DOT & IATA : PAINT RELATED MATERIAL, 3, UN1263, PG II, LABEL REQUIRED: FLAMMABLE LIQUID.

15.0 REGULATORY INFORMATION

TSCA Status: All components in this product are on the TSCA Inventory.

Chemical Name	CAS #	Regulation	%Range
Methanol	67-56-1	CERCLA	0.5-1.5
Methanol	67-56-1	SARA 313	0.5-1.5
Ethanol		Prop 65	

Substances known to the State of California to cause cancer or reproductive harm: Ethanol.

16.0 ADDITIONAL INFORMATION

Other Info	Prepared by Thomas J. Lewis Ph.D.
Disclaimer	<p>The information contained in this safety data sheet is provided in accordance with the requirements of OSHA Hazard Communication (29 CFR 1910.1200). The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written instructions. As the specific conditions of use of the product are outside of the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.</p> <p>The information contained in this Material Safety Data Sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance as suitability for particular applications.</p>